

EFD 2412/...-RSMA


End-Fed $\frac{1}{2} \lambda$ Dipole Antenna with RSMA-Connector for Portable Equipment in the 2400 MHz Band

DESCRIPTION

- End-fed $\frac{1}{2} \lambda$ whip – groundplane independent.
- High gain and efficient decoupling from the portable equipment due to half-wave design.
- 5 dB gain compared to a $\frac{1}{4} \lambda$ antenna whip on the same equipment.
- Highest quality materials in a long-lasting and durable design.
- Models available for the ISM, RLAN, WLAN systems.
- Provided with RSMA connector.



RSMA CONNECTOR DETAILS



Female inner conductor

ORDERING DESIGNATIONS

TYPE	PRODUCT NO.
EFD 2412/...-RSMA	140000229

When ordering the antenna, please state the centre frequency.

SPECIFICATIONS

ELECTRICAL	
MODEL	EFD 2412/...-RSMA
ANTENNA TYPE	End-fed $\frac{1}{2} \lambda$ antenna for portable equipment
FREQUENCY	To be specified within 2350 - 2550 MHz
IMPEDANCE	Nom. 50 Ω
POLARIZATION	Vertical
GAIN	5 dB (compared to a $\frac{1}{4} \lambda$ portable antenna on the same equipment)
BANDWIDTH	≥ 100 MHz @ SWR ≤ 1.7
SWR	< 1.3 @ f. res.
MAX. POWER	25 W
MECHANICAL	
MATERIALS	Black cover POM Black-chromed brass
COLOUR	Black
TOTAL HEIGHT	Approx. 110 mm
WEIGHT	Approx. 22 g
CONNECTOR	RSMA



PROCOM France S.A.R.L. se réserve le droit d'améliorer les spécifications sans préavis.

15/08/11